UNICORE Gateway





UNICORE GATEWAY

UNICORE Team

Document Version:	1.1.0
Component Version:	7.6.0
Date:	16 03 2016

This work is co-funded by the EC EMI project under the FP7 Collaborative Projects Grant Agreement Nr. INFSO-RI-261611.

PDF BY DBLATEX

Contents

1	Intr	oduction	1
2	Inst	allation	2
	2.1	Installation from the core server bundle	2
	2.2	Installation from a Linux package (rpm or deb)	2
3	Upg	rading	3
4	Con	figuration	3
	4.1	Java and environment settings: startup.properties	3
	4.2	Configuring sites: connections.properties	3
	4.3	Main server settings: gateway.properties	4
	4.4	Certificate-less end-user access	4
	4.5	security.properties	11
	4.6	Logging	18
5	Usin	g Apache httpd as a frontend	21
6	Usin	g the Gateway for failover and/or loadbalancing of UNICORE sites	21
	6.1	Configuration	21
	6.2	Available Strategies	22
7	Gate	eway failover and migration	23
	7.1	Gateway's migration	23
	7.2	Failover and loadbalancing of the Gateway	23
8	Buil	ding the Gateway from source	24

This user manual provides information on running and using the UNICORE gateway. Please note also the following places for getting more information:

UNICORE Website: http://www.unicore.eu

Support list: unicore-support@lists.sf.net

Developer's list: unicore-devel@lists.sf.net

1 Introduction

The Gateway is the entry point into a UNICORE site, routing HTTPS traffic to servers like UNI-CORE/X. It is installed in front of any networking firewall. It authenticates incoming messages and forwards them to their intended destination. The Gateway receives the reply and sends it back to the client. In this way, only a single open port in a site's firewall has to be configured.

LIMITATIONS

This forwarding process only works for "most" HTTP requests, and is not a complete HTTP reverse proxy implementation. For example, it is not possible to run a full, complex web application like the UNICORE portal "behind" the gateway. Check the respective components's manual whether it can be run behind the Gateway.

In effect, traffic to a *virtual* URL, e.g. *https://mygateway:8088/Alpha* is forwarded to the real URL, e.g. *https://host1:7777*.

The mappings of virtual URL to real URL for the available sites are listed in a configuration file connections.properties. Additionally, the gateway supports dynamic registration of sites.

The second functionality of the gateway is authentication of incoming requests. Connections to the gateway are made using client-authenticated SSL, so the gateway will check whether the caller presents a certificate issued by a trusted authority. Information about the authenticated client is forwarded to services behind the gateway in UNICORE proprietary format (as SOAP header element).

IMPORTANT NOTE ON PATHS

The UNICORE Gateway is distributed either as a platform independent and portable bundle (as a part of the UNICORE core server package) or as an installable, platform dependent package format such as RPM.

Depending on the installation method, the paths to various Gateway files are different. If installing using a distribution-specific package the following paths are used:

```
CONF=/etc/unicore/gateway
BIN=/usr/sbin
LOG=/var/log/unicore/gateway
```

If installing using the portable bundle all Gateway files are installed under a single directory. Path prefixes then are as follows, where INST is a directory where the Gateway was installed:

```
CONF=INST/conf
BIN=INST/bin
LOG=INST/log
```

The above variables (CONF, BIN and LOG) are used throughout the rest of this manual.

2 Installation

The UNICORE Gateway is distributed in the following formats:

- 1. As a part of platform independent installation bundle called UNICORE core server bundle. The UNICORE core server bundle is provided in two forms: one with a graphical installer and one with a command line installer.
- 2. As a binary, platform-specific package available currently for RedHat (Centos) and Debian platforms. Those packages are not tested on all possible platforms, but should work without any problems with other versions of similar distributions, e.g. SL6, Centos, or Fedora.

2.1 Installation from the core server bundle

Download the core server bundle from the UNICORE project website.

If you use the graphical installer, follow the on-screen instructions and do not forget to enable the Gateway checkbox when prompted.

If you use the console installer, please review the README file available after extracting the bundle. You don't have to change any defaults as the Gateway is installed by default.

2.2 Installation from a Linux package (rpm or deb)

Use your distribution's package manager to install.

3 Upgrading

The general update procedure is presented below, with possible variations:

- 1. Stop the old Gateway.
- 2. Update the server package. This step mostly applies for RPM/DEB managed installations. For Quickstart installation it is enough to replace the *.jar files with the new ones.
- 3. Start the newly installed Gateway.
- 4. Verify log file and fix any problems reported.

4 Configuration

The gateway is configured using a set of configuration files, which reside in the CONF subdirectory.

4.1 Java and environment settings: startup.properties

This file contains settings related to the Java VM, such as the Java command to use, memory settings, library paths etc.

4.2 Configuring sites: connections.properties

This is a simple list connecting the names of sites and their physical addresses. An example is:

```
DEMO-SITE = https://localhost:7777
REGISTRY = https://localhost:7778
```

If this file is modified, the gateway will re-read it at runtime, so there is no need to restart the gateway in order to add or remove sites.

Optionally administrator can enable a possibility for dynamic site registration at runtime, see Section 4.4.2 for details. Then this file should contain only the static entries (or none if all sites register dynamically).

Further options for back-end sites configuration are presented in Section 6.

4.3 Main server settings: gateway.properties

Use the gateway.hostname property to configure the network interface and port the gateway will listen on. You can also select between https and http protocol, though in almost all cases https will be used.

Example:

gateway.hostname = https://192.168.100.123:8080

Note

If you set the host to 0.0.0.0, the gateway will listen on all network interfaces of the host machine, else it will listen only on the specified one.

If the scheme of the hostname URL is set to https, the Gateway uses the configuration data from security.properties to configure the HTTPS settings.

4.4 Certificate-less end-user access

With UNICORE 7, it is possible that end-users do not have client certificates. To enable them to connect, the Gateway needs to accept TLS connections without a client certificate. To configure this, set the following in gateway.properties

```
gateway.httpServer.requireClientAuthn=false
```

4.4.1 Scalability settings

To fine-tune the operational parameters of the embedded Jetty server, you can set advanced HTTP server parameters. See Section 4.4.5 for details. Among others you can use the nonblocking IO connector offered by Jetty, which will scale up to higher numbers of concurrent connections than the default connector.

The gateway acts as a https client for the VSites behind it. The number of concurrent calls is limited, and controlled by two parameters:

```
# maximum total number of concurrent calls to Vsites
gateway.client.maxTotal=100
# total number of concurrent calls per site
gateway.client.maxPerService=20
```

You can also control the limit on the maximum SOAP header size which is allowed by the gateway. **Typically you don't have to touch this parameter**. However if your clients do produce very big SOAP headers and gateway blocks them, you can increase the limit. Note that such a giant SOAP header usually means that the client is not behaving in a sane way, e.g. is trying to perform a DoS attack.

```
# maximum size of an accepted SOAP header, in bytes
gateway.soapMaxHeader=102400
```

Note that gateway may consume this amount of memory (plus some extra amount for other data) for each opened connection. Therefore, this value multiplied by the number of maximum allowed connections, should be significantly lower, then the total memory available for the gateway.

4.4.2 Dynamic registration of Vsites

Dynamic registration is controlled by three properties in CONF/gateway.properties file:

gateway.registration.enable=true

If set to true, the gateway will accept dynamic registrations which are made by sending a HTTP POST request to the URL /VSITE_REGISTRATION_REQUEST

Filters can be set to forbid access of certain hosts, or to require certain strings in the Vsite addresses. For example:

gateway.registration.deny=foo.org example.org

will deny registration if the remote hostname contains foo.org or example.org. Conversely,

gateway.registration.allow=mydomain.org

will only accept registrations if the remote address contains *mydomain.org*. These two (deny and allow) can be combined.

4.4.3 Web interface ("monkey page")

For testing and simple monitoring purposes, the gateway displays a website showing detailed site information (the details view can be disabled). Once the Gateway is running, open up a browser and navigate to https://<gateway_host>:8080 (or whichever URL the gateway is running on). As the gateway usually runs using SSL, you will need to import a suitable client certificate into your web browser.

A HTML form for testing the dynamic registration is available as well, by clicking the link in the footer of the main gateway page.

To disable the Vsite details page, set

gateway.disableWebpage=true

4.4.4 Main options reference

UNICORE Gateway

Property name	Туре	Default value / mandatory	Description
gateway.hostname	string	mandatory to be set	external gateway bind address
gateway. registration. allow	string	-	Space separated list of allowed hosts for dynamic registration.
gateway. registration. deny	string	-	Space separated list of denied hosts for dynamic registration.
gateway. registration. enable	[true, false]	false	Whether dynamic registration of sites is enabled.
	Passing Co.	nsignor info	
gateway. consignorTokenTi meTolerance	integer >= 0	30	The validity time of the authenticated client information passed to backend sites will start that many seconds before the real authentication. It is used to mask time synchronization problems between machines.
gateway.consigno rTokenValidity	integer >= 1	60	What is the validity time of the authenticated client information passed to backend sites. Increase it if there machines clocks are not synhronized.
gateway.signCons ignorToken	[true, false]	false	Controls whether information about the authenticated client (the consignor) passed to backend sites should be signed, or not. Signing is slower, but is required when sites may be reached directly, bypassing the Gateway.
		→ Site client	
gateway.client. chunked	[true, false]	true	Controls whether chunked passing of HTTP requests to backend sites is supported.

Property name	Туре	Default value / mandatory	Description
gateway.client. connectionTime out	integer number	30000	Connection timeout, used when connecting to backend sites.
gateway.client. expectContinue	[true, false]	true	Controls whether the HTTP expec-continue mechanism is enaled on connections to backend sites.
gateway.client. gzip	[true, false]	true	Controls whether support for compression is announced to backend sites.
gateway.client. keepAlive	[true, false]	true	Whether to keep alive the connections to backend sites.
gateway.client. maxPerService	integer number	20	Maximum allowed number of connections per backend site.
gateway.client. maxTotal	integer number	100	Maximum total number of connections to backend sites allowed.
gateway.client. socketTimeout	integer number	30000	Connection timeout, used when connecting to backend sites.
	Adva	inced	·
gateway. disableWebpage	[true, false]	false	Whether the (so called monkey) status web page should be disabled.
gateway. externalHostname	string	not set	External address of the gateway, when it is accessible through a frontend server as Apache HTTP.
gateway. soapMaxHeader	integer [1024 — 1024000000]	102400	Size in bytes of the accepted SOAP header. In the most cases you don't need to change it.

4.4.5 Configuring advanced HTTP server settings

UNICORE servers are using an embedded Jetty HTTP server. In most cases the default configuration should be perfectly fine. However, for some sites (e.g. experiencing an extremely high load) HTTP server settings can be fine-tuned with the following parameters.

Property name	Туре	Default value / mandatory	Description
gateway. httpServer.disab ledCipherSuites	string	empty string	Space separated list of SSL cipher suites to be disabled. Names of the ciphers must adhere to the standard Java cipher names, available here: http://docs.oracle.com/- javase/8/docs/technotes/- guides/security/- SunProviders.html#SupportedCipherSuite
gateway. httpServer. enableHsts	[true, false]	false	Control whether HTTP strict transport security is enabled. It is a good and strongly suggested security mechanism for all production sites. At the same time it can not be used with self-signed or not issued by a generally trusted CA server certificates, as with HSTS a user can't opt in to enter such site.
gateway. httpServer. fastRandom	[true, false]	false	Use insecure, but fast pseudo random generator to generate session ids instead of secure generator for SSL sockets.
gateway. httpServer.gzip. enable	[true, false]	false	Controls whether to enable compression of HTTP responses.
gateway. httpServer.gzip. minGzipSize	integer number	100000	Specifies the minimal size of message that should be compressed.

UNICORE Gateway

Property name	Туре	Default value / mandatory	Description
gateway. httpServer.highL oadConnections	integer number	200	If the number of connections exceeds this amount, then the connector is put into a special <i>low on</i> <i>resources</i> state. Existing connections will be closed faster. Note that the server will also go to the low on resources mode if there are no available threads in the pool. You can set this to 0 to disable the connections limit (and have only thread pool size governed limit). If set to a negative number then the <i>low on resources</i> mode won't be used at all.
gateway. httpServer. lowResourceMaxId leTime	integer >= 1	100	In low resource conditions, time (in ms.) before an idle connection will time out.
gateway. httpServer. maxIdleTime	integer >= 1	200000	Time (in ms.) before an idle connection will time out. It should be large enough not to expire connections with slow clients, values below 30s are getting quite risky.
gateway. httpServer. maxThreads	integer number	255	Maximum number of threads to have in the thread pool for processing HTTP connections. Note that this number will be increased with few additional threads to handle connectors.
gateway. httpServer. minThreads	integer >= 1	1	Minimum number of threads to have in the thread pool for processing HTTP connections. Note that this number will be increased with few additional threads to handle connectors.

UNICORE Gateway

Property name	Туре	Default value / mandatory	Description
gateway. httpServer.requi reClientAuthn	[true, false]	true	Controls whether the SSL socket requires client-side authentication.
gateway. httpServer. soLingerTime	integer number	-1	Socket linger time.
gateway. httpServer. useNIO	[true, false]	true	DEPRECATED, no effect
gateway. httpServer. wantClientAuthn	[true, false]	true	Controls whether the SSL socket accepts (but does not require) client-side authentication.
gateway. httpServer. xFrameAllowed	string	http:// localh ost	URI origin that is allowed to embed web interface inside a (i)frame. Meaningful only if the xFrameOptions is set to <i>allowFrom</i> . The value should be in the form: <i>http[s]://host[:port]</i>
gateway. httpServer. xFrameOptions	[deny, sameOrigin, allowFrom, allow]	deny	Defines whether a clickjacking prevention should be turned on, by insertionof the X-Frame-Options HTTP header. The <i>allow</i> value disables the feature. See the RFC 7034 for details. Note that for the <i>allowFrom</i> you should define also the xFrameAllowed option and it is not fully supported by all the browsers.

Example

Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

In this example we will turn on compression of all responses bigger than 50kB (assuming that the client supports decompression). Additionally we are limiting the number of concurrent clients that can be served to more or less 50, while keeping 10 threads ready all the time to server new clients quicker.

```
jetty.gzip.enable=true
jetty.gzip.minGzipSize=51200
jetty.maxThreads=50
jetty.minThreads=10
```

4.5 security.properties

In the security.properties file, the trust store and gateway credential is configured.

4.5.1 Configuring PKI trust settings

Public Key Infrastructure (PKI) trust settings are used to validate certificates. This is performed, in the first place when a connection with a remote peer is initiated over the network, using the SSL (or TLS) protocol. Additionally certificate validation can happen in few other situations, e.g. when checking digital signatures of various sensitive pieces of data.

Certificates validation is primarily configured using a set of initially trusted certificates of so called Certificate Authorities (CAs). Those trusted certificates are also known as *trust anchors* and their collection is called a *trust store*.

Except of *trust anchors* validation mechanism can use additional input for checking if a certificate being checked was not revoked and if its subject is in a permitted namespace.

UNICORE allows for different types of trust stores. All of them are configured using a set of properties.

- *Keystore trust store* the only format supported in older UNICORE versions. Trusted certificates are stored in a single binary file in JKS or PKCS12 format. The file can be only manipulated using a special tool like JDK *keytool* or openssl (in case of PKCS12 format). This format is great if trust store should be in a single file or when compatibility with other Java solutions or older UNICORE releases is desired.
- OpenSSL trust store allows to use a directory with CA certificates stored in PEM format, under precisely defined names: the CA certificates, CRLs, signing policy files and namespaces files are named <hash>.0, <hash>.r0, <hash>.signing_policy and <hash>.namespaces. Hash is the old hash of the trusted CA certificate subject name (in Openssl version > 1.0.0 use -suject_hash_old switch to generate it). If multiple certificates have the same hash then the default zero number must be increased. This format is the same as used by other then UNICORE popular middlewares as Globus and gLite. It is suggested when a common trust store with such middlewares is needed.

• *Directory trust store* - the most flexible and convenient option, suggested for all remaining cases. It allows to use a list of wildcard expressions, concrete paths of files or even URLs to remote files as a set of trusted CAs and in the same way for the CRLs. With this trust store administrator can simply configure all files (or all with a specified extension) in a directory to be used as a trusted certificates.

Property name	Туре	Default value / mandatory	Description
gateway.	[ALLOW,	ALLOW	Controls whether proxy
truststore.	DENY]		certificates are supported.
allowProxy		-	
gateway.	[keystore,	mandatory	The truststore type.
truststore.type	openssl, directory]	to be set	
gateway.	integer number	600	How often the truststore
truststore.			should be reloaded, in
updateInterval			seconds. Set to negative
			value to disable refreshing
			at runtime. (runtime
			updateable)
		ype settings	~
gateway.	integer number	15	Connection timeout for
truststore.			fetching the remote CA
directoryConnect			certificates in seconds.
ionTimeout	filesystem path		Directory where CA
gateway. truststore.	incsystem path	-	certificates should be
directoryDiskCac			cached, after downloading
hePath			them from a remote source.
neraen			Can be left undefined if no
			disk cache should be used.
			Note that directory should
			be secured, i.e. normal
			users should not be allowed
			to write to it.
gateway.	[PEM, DER]	PEM	For directory truststore
truststore.direc			controls whether
toryEncoding			certificates are encoded in
			PEM or DER.

Property name	Туре	Default value / mandatory	Description
gateway.	list of	-	List of CA certificates
truststore.direc	properties with		locations. Can contain
toryLocations.*	a common		URLs, local files and
	prefix		wildcard expressions.
			(runtime updateable)
	Keystore ty	pe settings	
gateway.	string	-	The keystore type (jks,
truststore.			pkcs12) in case of truststore
keystoreFormat			of keystore type.
gateway.	string	-	The password of the
truststore.			keystore type truststore.
keystorePassword			
gateway.	string	-	The keystore path in case of
truststore.			truststore of keystore type.
keystorePath			
		pe settings	
gateway.	[true, false]	false	In case of openssl
truststore.opens			truststore, specifies whether
slNewStoreFormat			the trust store is in openssl
			1.0.0+ format (true) or
			older openssl 0.x format
			(false)
gateway.	[GLOBUS_EUG	RHORMADPM	In case of openssl
truststore.	EU-	A_GLOBUS	truststore, controls which
opensslNsMode	GRIDPMA_GLC	BUS,	(and in which order)
	GLOBUS,		namespace checking rules
	EUGRIDPMA,		should be applied. The
	GLOBUS_EUGF	IDPMA_REQ	U RHQ UIRE settings will
	EU-		cause that all configured
	GRIDPMA_GLC	BUS_REQUI	Enamespace definitions files
	GLOBUS_REQU	JIRE,	must be present for each
	EU-		trusted CA certificate
	GRIDPMA_REQ	UIRE,	(otherwise checking will
	EU-		fail). The AND settings will
	GRIDPMA_ANI	_GLOBUS,	cause to check both existing
	EU-		namespace files. Otherwise
	GRIDPMA_ANI	_GLOBUS_R	EQNE IRE, found is checked
	IGNORE]		(in the order defined by the
			property).

Property name	Туре	Default value / mandatory	Description
gateway. truststore. opensslPath	filesystem path	/etc/ grid-sec urity/ certific ates	Directory to be used for opeenssl truststore.
	Revocatio	on settings	
gateway. truststore.crlCo nnectionTimeout	integer number	15	Connection timeout for fetching the remote CRLs in seconds (not used for Openssl truststores).
gateway. truststore. crlDiskCachePath	filesystem path	-	Directory where CRLs should be cached, after downloading them from remote source. Can be left undefined if no disk cache should be used. Note that directory should be secured, i.e. normal users should not be allowed to write to it. Not used for Openssl truststores.
gateway. truststore. crlLocations.*	list of properties with a common prefix	-	List of CRLs locations. Can contain URLs, local files and wildcard expressions. Not used for Openssl truststores. (<i>runtime</i> updateable)
gateway. truststore. crlMode	[REQUIRE, IF_VALID, IGNORE]	IF_VALID	General CRL handling mode. The IF_VALID setting turns on CRL checking only in case the CRL is present.
gateway. truststore.crlUp dateInterval	integer number	600	How often CRLs should be updated, in seconds. Set to negative value to disable refreshing at runtime. (<i>runtime updateable</i>)
gateway. truststore. ocspCacheTtl	integer number	3600	For how long the OCSP responses should be locally cached in seconds (this is a maximum value, responses won't be cached after expiration)

Property name	Туре	Default value / mandatory	Description
gateway. truststore. ocspDiskCache	filesystem path	-	If this property is defined then OCSP responses will be cached on disk in the defined folder.
<pre>gateway. truststore.ocspL ocalResponders. <number></number></pre>	list of properties with a common prefix	-	Optional list of local OCSP responders
gateway. truststore. ocspMode	[REQUIRE, IF_AVAILABLE, IGNORE]	IF_AVAIL ABLE	General OCSP ckecking mode. REQUIRE should not be used unless it is guaranteed that for all certificates an OCSP responder is defined.
gateway. truststore. ocspTimeout	integer number	10000	Timeout for OCSP connections in miliseconds.
gateway. truststore. revocationOrder	[CRL_OCSP, OCSP_CRL]	OCSP_CRL	Controls overal revocation sources order
gateway. truststore. revocationUseAll	[true, false]	false	Controls whether all defined revocation sources should be always checked, even if the first one already confirmed that a checked certificate is not revoked.

Examples

Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

Directory trust store, with a minimal set of options:

```
truststore.type=directory
truststore.directoryLocations.l=/trust/dir/*.pem
truststore.crlLocations=/trust/dir/*.crl
```

Directory trust store, with a complete set of options:

```
truststore.type=directory
truststore.allowProxy=DENY
truststore.updateInterval=1234
truststore.directoryLocations.1=/trust/dir/*.pem
truststore.directoryLocations.2=http://caserver/ca.pem
truststore.directoryEncoding=PEM
truststore.directoryConnectionTimeout=100
truststore.directoryDiskCachePath=/tmp
truststore.crlLocations.1=/trust/dir/*.crl
truststore.crlLocations.2=http://caserver/crl.pem
truststore.crlUpdateInterval=400
truststore.crlMode=REQUIRE
truststore.crlConnectionTimeout=200
truststore.crlDiskCachePath=/tmp
```

Openssl trust store:

```
truststore.type=openssl
truststore.opensslPath=/truststores/openssl
truststore.opensslNsMode=EUGRIDPMA_GLOBUS_REQUIRE
truststore.allowProxy=ALLOW
truststore.updateInterval=1234
truststore.crlMode=IF_VALID
```

Java keystore used as a trust store:

```
truststore.type=keystore
truststore.keystorePath=src/test/resources/certs/truststore. ↔
jks
truststore.keystoreFormat=JKS
truststore.keystorePassword=xxxxxx
```

4.5.2 Configuring the credential

UNICORE uses private key and a corresponding certificate (called together as a *credential*) to identify users and servers. Credentials might be provided in several formats:

- Credential can be obtained from a keystore file, encoded in JKS or PKCS12 format.
- Credential can be loaded as a pair of PEM files (one with private key and another with certificate),
- or from a pair of DER files,
- or even from a single file, with PEM-encoded certificates and private key (in any order).

The following table list all parameters which allows for configuring the credential. Note that nearly all options are optional. If not defined, the format is tried to be guessed. However some credential formats require additional settings. For instance if using *der* format the *keyPath* is mandatory as you need two DER files: one with certificate and one with the key (and the latter can not be guessed).

Property name	Туре	Default value / mandatory	Description
gateway. credential.path	filesystem path	mandatory to be set	Credential location. In case of <i>jks</i> , <i>pkcs12</i> and <i>pem</i> store it is the only location required. In case when credential is provided in two files, it is the certificate file path.
gateway. credential. format	[jks, pkcs12, der, pem]	-	Format of the credential. It is guessed when not given. Note that <i>pem</i> might be either a PEM keystore with certificates and keys (in PEM format) or a pair of PEM files (one with certificate and second with private key).
gateway. credential. password	string	-	Password required to load the credential.
gateway. credential. keyPath	string	-	Location of the private key if stored separately from the main credential (applicable for <i>pem</i> and <i>der</i> types only),
gateway. credential. keyPassword	string	-	Private key password, which might be needed only for <i>jks</i> or <i>pkcs12</i> , if key is encrypted with different password then the main credential password.
gateway. credential. keyAlias	string	-	Keystore alias of the key entry to be used. Can be ignored if the keystore contains only one key entry. Only applicable for <i>jks</i> and <i>pkcs12</i> .

Examples

Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

Credential as a pair of DER files:

```
credential.format=der
credential.password=the\!njs
credential.path=/etc/credentials/cert-1.der
credential.keyPath=/etc/credentials/pk-1.der
```

Credential as a JKS file (credential type can be autodetected in almost every case):

```
credential.path=/etc/credentials/server1.jks
credential.password=xxxxxx
```

4.5.3 Proxy certificate support

The UNICORE gateway optionally accepts proxy certificates as used by other Grid middleware systems. In general, we think proxies are a bad idea, but for interoperability purposes, proxies support can be enabled. If enabled, the clients using proxies are authenticated as the initial issuer of the presented proxy certificates chain. See the above reference properties table for the actual setting.

4.6 Logging

UNICORE uses the Log4j logging framework. It is configured using a config file. By default, this file is found in components configuration directory and is named logging.propert ies. The config file is specified with a Java property log4j.configuration (which is set in startup script).

Several libraries used by UNICORE also use the Java utils logging facility (the output is twolines per log entry). For convenience its configuration is also controlled in the same logging. properties file and is directed to the same destination as the main Log4j output.

Note

You can change the logging configuration at runtime by editing the logging.properties file. The new configuration will take effect a few seconds after the file has been modified.

By default, log files are written to the the LOGS directory.

The following example config file configures logging so that log files are rotated daily.

```
# Set root logger level to INFO and its only appender to A1.
log4j.rootLogger=INFO, A1
# A1 is set to be a rolling file appender with default params
log4j.appender.A1=org.apache.log4j.DailyRollingFileAppender
log4j.appender.A1.File=logs/uas.log
#configure daily rollover: once per day the uas.log will be copied
#to a file named e.g. uas.log.2008-12-24
log4j.appender.A1.DatePattern='.'yyyyy-MM-dd
# A1 uses the PatternLayout
log4j.appender.A1.layout=org.apache.log4j.PatternLayout
log4j.appender.A1.layout.ConversionPattern=%d [%t] %-5p %c{1} %x - 
%m%n
```

Note

In Log4j, the log rotation frequency is controlled by the DatePattern. Check http://logging.apache.org/log4j/1.2/apidocs/org/apache/log4j/DailyRollingFileAppender.html for the details.

For more info on controlling the logging we refer to the log4j documentation:

- PatternLayout
- RollingFileAppender
- DailyRollingFileAppender

Log4j supports a very wide range of logging options, such as date based or size based file rollover, logging different things to different files and much more. For full information on Log4j we refer to the publicly available documentation, for example the Log4j manual.

4.6.1 Logger categories, names and levels

Logger names are hierarchical. In UNICORE, prefixes are used (e.g. "unicore.security") to which the Java class name is appended. For example, the XUUDB connector in UNICORE/X logs to the "unicore.security.XUUDBAuthoriser" logger.

Therefore the logging output produced can be controlled in a fine-grained manner. Log levels in Log4j are (in increasing level of severity):

TRACE on this level *huge* pieces of unprocessed information are dumped, # DEBUG on this level UNICORE logs (hopefully) admin-friendly, verbose information, useful for hunting problems, # INFO standard information, not much output, # WARN warnings are logged when something went wrong (so it should be investigated), but recovery was possible, # ERROR something went wrong and operation probably failed, # FATAL something went really wrong - this is used very rarely for critical situations like server failure.

For example, to debug a security problem in the UNICORE security layer, you can set:

```
log4j.logger.unicore.security=DEBUG
```

If you are just interested in details of credentials handling, but not everything related to security you can use the following:

```
log4j.logger.unicore.security=INFO
log4j.logger.unicore.security.CredentialProperties=DEBUG
```

so the XUUDBAuthoriser will log on DEBUG level, while the other security components log on INFO level.

Note

(so the full category is printed) and turn on the general DEBUG logging for a while (on unicore). Then interesting events can be seen and subsequently the logging configuration can be fine tuned to only show them.

The most important, root log categories used by the Gateway's logging are:

unicore.gateway	General gateway logging	
unicore.connections	nections Log IPs of clients, and the DN after the	
	SSL handshake	
unicore.httpserver	HTTP processing, Jetty server	
unicore.security	Certificate details and other security	

The Gateway uses the so called MDC (Mapped Diagnostic Context) to provide additional information on the client which is served. In the MDC the client's IP address and client's Distinguished Name is stored. You can control whether to attach MDC to each line by the <code>%X{entry} log4j</code> pattern entry. As the entry you can use: clientIP or clientName. For example:

```
log4j.appender.Al.layout.ConversionPattern=%d [%t] [%X{clientIP} %X ↔
{clientName}] %-5p %c{1} - %m%n
```

5 Using Apache httpd as a frontend

You may wish to use the Apache webserver (httpd) as a frontent for the gateway (e.g. for security or fault-tolerance reasons).

Requirements

- Apache httpd
- mod_proxy for Apache httpd

External references

https://wiki.eclipse.org/Jetty/Howto/Configure_mod_proxy

6 Using the Gateway for failover and/or loadbalancing of UNI-CORE sites

The Gateway can be used as a simple failover solution and/or loadbalancer to achieve high availability and/or higher scalability of UNICORE/X sites without additional tools.

A site definition (in CONF/connections.properties) can be extended, so that multiple physical servers are used for a single virtual site.

An example for such a so-called multi-site declaration in the connections.properties file looks as follows:

```
#declare a multisite with two physical servers
MYSITE=multisite:vsites=https://localhost:7788 https://localhost ↔
:7789
```

This will tell the gateway that the virtual site "MYSITE" is indeed a multi-site with the two given physical sites.

6.1 Configuration

Configuration options for the multi-site can be passed in two ways. On the one hand they can go into the connections.properties file, by putting them in the multi-site definition, separated by ";" characters:

```
#declare a multisite with parameters
```

MYSITE=multisite:param1=value1;param2=value2;param3=value3;...

The following general parameters exist

vsites	List of physical sites
strategy	Class name of the site selection strategy to
	use (see below)
config	Name of a file containing additional
	parameters

Using the "config" option, all the parameters can be placed in a separate file for enhanced readability. For example you could define in connections.properties:

#declare a multisite with parameters read from a separate file

MYSITE=multisite:config=conf/mysite-cluster.properties

and give the details in the file "conf/mysite-cluster.properties":

```
#example multisite configuration
vsites=https://localhost:7788 https://localhost:7789
```

```
#check site health at most every 5 seconds
strategy.healthcheck.interval=5000
```

6.2 Available Strategies

A selection strategy is used to decide where a client request will be routed. By default, the strategy is "Primary with fallback", i.e. the request will go to the first site if it is available, otherwise it will go to the second site.

Primary with fallback

This strategy is suitable for a high-availability scenario, where a secondary site takes over the work in case the primary one goes down for maintenance or due to a problem. This is the default strategy, so nothing needs to be configured to enable it. If you want to explicitly enable it anyway, set

strategy=primaryWithFallback

The strategy will select from the first two defined physical sites. The first, primary one will be used if it is available, else the second one. Health check is done on each request, but not more frequently as specified by the "strategy.healthcheck.interval" parameter. By default, this parameter is set to 5000 milliseconds.

Changes to the site health will be logged at "INFO" level, so you can see when the sites go up or down.

Round robin

This strategy is suitable for a load-balancing scenario, where a random site will be chosen from the available ones. To enable it, set

strategy=roundRobin

Changes to the site health will be logged at "INFO" level, so you can see when the sites go up or down.

It is very important to be aware that this strategy requires that all backend sites used in the pool, share a common persistence. It is because Gateway does not track clients, so particular client requests may land at different sites. This is typically solved by using a non-default, shared database for sites, such as MySQL.

Note

Currently loadbalancing of target sites is an experimental feature and is not yet fully functional. It will be improved in future UNICORE versions.

Custom strategy

You can implement and use your own failover strategy, in this case, use the name of the Java class as strategy name:

strategy=your_class_name

7 Gateway failover and migration

The Section 6 covered usage of the Gateway to provide failover of backend services. However it may be needed to guarantee high-availability for the Gateway itself or to move it to other machine in case of the original one's failure.

7.1 Gateway's migration

The Gateway does not store any state information, therefore its migration is easy. It is enough to install the Gateway at the target machine (or even to simply copy it in the case of installation from the core server bundle) and to make sure that the original Gateway's configuration is preserved.

If the new machine uses a different address, it needs to be reflected in the server's configuration file (the listen address). Also, the configuration of sites behind the gateway must be updated accordingly.

7.2 Failover and loadbalancing of the Gateway

Gateway itself doesn't provide any features related to its own redundancy. However as it is stateless, the standard redundancy solutions can be used.

The simpliest solution is to use Round Robin DNS, where DNS server routes the Gateway's DNS address to a pool of real IP addresses. While easy to set up this solution has a significant drawback: DNS server doesn't care about machines being down.

The much better choice is to use the Linux-HA software suite, often known under the name of its principal component, the *heartbeat*. For details see http://www.linux-ha.org

Additionally a more advanced HTTP-aware software can be used, such as HA-Proxy (http://haproxy.1wt.eu). Currently Gateway and UNICORE don't maintain HTTP sessions so usage of the HTTP-aware load-balancer is not strictly required, but such solutions generally provide more general purpose features.

8 Building the Gateway from source

To checkout the latest version of the Gateway source code, do

```
svn co http://unicore.svn.sourceforge.net/svnroot/unicore/gateway/ ↔
    trunk gateway
```

You will need to install Maven from http://maven.apache.org Compile using

mvn install

Compiles the code and runs the tests.

The file "README-building.txt" contains instructions for building distributable packages.