



# **XUUDB MANUAL**

**UNICORE** Team

Document Version:	2.1.1
Component Version:	2.3.2
Date:	13 11 2017

This work is co-funded by the EC EMI project under the FP7 Collaborative Projects Grant Agreement Nr. INFSO-RI-261611.

PDF BY DBLATEX

# Contents

1	Ove	rview	1
	1.1	The classic mapping	1
	1.2	The dynamic mapping	2
2	Insta	allation	3
	2.1	Installation from Quickstart package	3
	2.2	Installation from RPM or DEB packages	4
3	Upg	rade from 1.x version	4
4	The	XUUDB server	5
	4.1	Security	5
	4.2	Administrative access	6
	4.3	Configuration	6
	4.4	Dynamic mappings configuration	20
	4.5	Starting the XUUDB server	26
	4.6	Stopping the server	27
	4.7	Logging	27
5	The	admin client	29
	5.1	Configuring advanced HTTP client settings	30
	5.2	Commands	33
	5.3	Adding entries using add or adddn	34
	5.4	Checking the content	34
	5.5	Removing entries	35
	5.6	Exporting/importing	35
	5.7	Updating entries	36

The XUUDB server is an Attribute Source implementation which can be used by UNICORE servers. It is used to map a Grid identity (an X500 distinguished name) to authorisation and incarnation attributes. The XUUDB is also capable of performing dynamic mappings of incarnation attributes, using a rule engine.

For more information about UNICORE visit http://www.unicore.eu.

# Overview

The UNICORE XUUDB is is used to map Grid user identity (an X.509 certificate or X.500 distinguished name (DN)) to a set of attributes. The attributes are typically used to provide local account details (uid, gid(s)) and sometimes also to provide authorization information: user's role.

The UNICORE XUUDB is best suited as a site-service. Theoretically it can be used for multiple sites, however as it offers limited authorization capabilities and doesn't allow for grouping users, it is better to use the more flexible Unity server in such a case. In case of the simple one host-service XUUDB sometimes can be replaced by a simple file storing the mappings. Please refer to the UNICORE/X documentation for more information.

The XUUDB offers two web services, one for querying, and one for administration of the users' database. There are several clients which can use the XUUDB server:

- Admin client (see Section 5) can be used to control the XUUDB database contents.
- UNICORE servers include the XUUDB client code (it is named XUUDB Attribute Information Point) and can consume and process the XUUDB information.
- UNICORE Rich client plugin allows for editing the XUUDB contents remotely, however it is not enabled by default and it is not always up to date so some features might be missing.

Both admin and client access to the XUUDB can be protected by a client-authenticated SSL.

The XUUDB can map users using two different mechanisms:

- *classic* or *static* mechanism, where administrator enters mappings for each DN (or certificate) manually,
- *dynamic* mechanism, where administrator only define rules stating what attributes should be assigned to Grid users fulfilling rule's condition.

## The classic mapping

The classic or static mechanism was the only one available in XUUDB 1.x. It is useful when number of users is small and easy to maintain or when UNICORE is used as a gateway to

HPC site, with a well defined set of users. It is also useful in Grid scenarios when a dedicated, external infrastructure is build to maintain a global list of users.

Using it it is possible to set a list of Unix logins (aka XLogins or uids), a list of UNIX groups (aka projects or gids) and the role attribute used for authorization. The first uid and the first gid is assumed to be the default one but Grid users are allowed to choose any of the available.

In case of the default authorization policy the *user* role is required to get a normal access to the site, the *admin* role grants super-user privileges, and the *banned* role bans the user.

The XUUDB stores and compares only distinguished names (DNs), not the full certificates.

Multiple Grid sites can share the XUUDB, even if the attributes are different per Grid site. Grid sites are grouped by the so-called GCID (grid component ID).

#### The dynamic mapping

The dynamic mechanism was introduced in XUUDB 2. It is used to map users who *were already authorized*, therefore it doesn't make sense (and is not possible) to assign the authorization attributes as *role*. The dynamic mechanism is useful in case of typical Grid deployments, when a site doesn't know a precise list of its users (which are maintained by the supported Virtual Organizations), or simply doesn't want to define manually a local account for each grid user. In other words, site rely on a trusted 3rd party (a Virtual Organization) to maintain a list of genuine and authorized users, and automatically assigns a local account to each user.

As it will be shown later on dynamic mappings can be also used in other scenarios, also being complementary to static mappings.

Dynamic mappings configuration is described in the section Section 4.4.

#### **IMPORTANT NOTE ON PATHS**

XUUDB is distributed either as an platform independent and portable bundle (as a part of UNICORE quickstart package) or as an installable, platform dependent package such as RPM.

Depending on the installation package used paths are different. If installing using distributionspecific package the following path prefixes are used:

```
CONF=/etc/unicore/xuudb
BIN=/usr/sbin
ADMIN=/usr/sbin/unicore-xuudb-admin
LOG=/var/log/unicore/xuudb
```

If installing using portable bundle all XUUDB's files are installed under a single directory. Path prefixes used then are as follows, where INST is a directory where XUUDB was installed:

```
CONF=INST/conf
BIN=INST/bin
ADMIN=BIN/admin.sh
LOG=INST/log
```

The above variables (CONF, BIN, ADMIN and LOG) are used throughout the rest of this manual.

# Installation

UNICORE XUUDB is distributed in the following formats:

- 1. As a part of platform independent installation bundle called UNICORE Quickstart. UNI-CORE Quickstart is provided in two forms: one with graphical installer and one with a command line installer.
- 2. As a binary, platform-specific packages available currently for RedHat (Centos) and Debian 6 platforms. Those packages are not tested on all possible platforms, but should work without any problems with other versions of similar distributions, e.g. SL6, Centos, or Fedora.

In both cases installation of XUUDB installs both XUUDB Server and XUUDB admin client.

After installing the server you will have to configure it. This is described in the section Section 4.

# Installation from Quickstart package

Download the quickstart bundle from the UNICORE project website.

If you use graphical installer follow the on screen instructions and do not forget to check the XUUDB checkbox when prompted.

If you use text installer then for generic installation instruction review the README file available after extracting the Quickstart bundle. You don't have to change any defaults as XUUDB installation is enabled by default.

In both cases you can preconfigure the XUUDB server during installation (of course this can be done also later) by choosing the XUUDB server host, port and mode.

# Installation from RPM or DEB packages

An up-to-date list of the available repositories is given on the following page https://sourceforge.net/p/unicore/wiki/Linux\_Repositories/

The preferred way is to use Yum or APT to install (and subsequently update) XUUDB.

After the repository is configured, the following command installs XUUDB:

\$> yum install unicore-xuudb

or in case of Debian systems

\$> apt-get install unicore-xuudb

# Upgrade from 1.x version

XUUDB 2 introduces a lot of new features and therefore the update form the version 1.x requires special attention. In particular:

- Configuration files format have changed for both xuudb\_server.conf and xuudb\_cl ient.conf
- New configuration file is required to configure dynamic mappings: dap-configurat ion.xml.
- Database schema in case of H2 was extended but also MySQL can be used (and other databases in future).

The general update procedure is presented below, with possible variations:

- 1. Dump database contents of the 1.x XUUDB using admin client export command.
- 2. Stop the 1.x XUUDB server.

- Update the server. This step mostly applies for RPM/DEB managed installations. For Quickstart installation it is advised to install XUUDB along with other needed components to a separate directory.
- 4. Port configuration of 1.x server to the new syntax. It can be done in two ways:
  - Manually by applying all old values to the new template configuration. There are only few properties to be ported so this is not a big task. The advantage of manual porting is that the new template files with new options and updated comments are used. Note: for RPM installations the new files will be named \*.rpmnew.
  - Automatically, using UNICORE configurator. You have to install the unicore-con figurator package. It is included in Quickstart, for distributions install, simply run appropriate command: yum install unicore-configurator or apt-get install unicore-configurator. Using the configurator you can update the old files automatically. Carefully read the output of the program there can be some problems reported. Option -h provides help, with information about the usage: how to perform dry run, how to recover files from backup etc.
    - For RPM/DEB installations it is enough to run unicore-config-update.py xuudb. NOTE that the automatic update tool will only update the default configuration files which are found in /etc/unicore/xuudb. In the case of xuudb-adminclient, the configuration file being actually used is stored in \$HOME/.xuudb/ xuudb\_client.conf. Therefore this file has to be updated manually. If the file in the home directory is supposed to be the same as the default, system-wide configuration, then it can be simply replaced.
    - For Quickstart put your old configuration files in the folder with the newly installed XUUDB and specify its directory with -c option: ./unicore-config-upd ate.py -c XUUDB\_CONFIG\_DIR xuudb.
- 5. If needed you can update your DB configuration to use MySQL.
- 6. Start the newly installed XUUDB.
- 7. Verify log file and fix any problems reported.
- 8. Use admin client to import the database dump created in the step 1.

# The XUUDB server

# Security

XUUDB server may be run using a plain HTTP port. Then there is no access control at all, so this mode is useful only in environments where XUUDB port is fully protected otherwise against unauthorised access.

Typically client-authenticated SSL is used to protect the XUUDB. For this you will need certificates for the XUUDB server and all Grid components that want to talk to the XUUDB. In general the UNICORE servers (like UNICORE/X) and the XUUDB-admin client need to connect to the XUUDB-server. To make the SSL connections possible, you have to put the following certificates as trusted certs into the XUUDB's server truststore:

- CA certificate(s) of the UNICORE/X server(s) that query the XUUDB
- CA certificate(s) of the XUUDB-admin user certificate(s)

and XUUDB's CA certificate in the truststores of its clients.

# Administrative access

The XUUDB provides two kinds of web service interfaces, one for querying the XUUDB (i.e. mapping Grid users to local users), and a second one for administration of the XUUDB (i.e. adding and editing entries). All access to the XUUDB (including the administration utility!) is through these web services. To prevent arbitrary Grid users from modifying the XUUDB, the administrative interface has to be protected.

To protect the administrative interface, an ACL file is used, which is a plain text file containing the distinguished names of the administrators. At least, it has to contain the DN of the certificate used by the administration utility.

As the static XUUDB data is rather sensitive (at least if privacy of the users is a concern) and dynamic mappings often require some local modifications (e.g. assigning an account from a pool) it is often desirable to protect also the query operations. XUUDB server since version 2, offers such option (see Section 4.3.1).

The ACL file can be changed at runtime to easily add or remove administrators.

To change the location of the ACL file, edit the server configuration and set a configuration parameter (see Section 4.3.1).

The ACL entries are expected in the RFC 2253 format. To get the name of a certificate in the correct format using openssl, you can use the following OpenSSL command:

```
$> openssl x509 -in demouser.pem -noout -subject -nameopt ↔
RFC2253
```

#### Configuration

By default, the configuration is defined in the file CONF/xuudb\_server.conf. To use a different configuration file, edit the start script, or use --start <config\_file> as command line arguments when starting.

The server's configuration file allows for setting the general XUUDB settings, database backend settings, advanced HTTP server settings and finally (for secure HTTPS URLs) the server's truststore and credential. The available properties are described in the following sections.

For production deployments you should review the listen address and setup correctly truststore and credential. Defaults for the embedded database configuration and HTTP server settings are usually fine. In case if you plan to use dynamic mappings, also the dynamic mapping rules need to be provided.

#### **Base server settings**

Property name	Туре	Default	Description
		value /	
		mandatory	
xuudb.aclFile	filesystem path	-	File with DNs of clients
			authorised to access
			protected XUUDB services.
xuudb.address	string	http://	HTTPS or HTTP URL
		localh	where the server should
		ost:	listen.
		34463	
xuudb.db.[.*]	string can have	-	Properties with this prefix
	subkeys		are used to configure
			database backend, used by
			XUUDB. See separate
			documentation for details.
xuudb.dynamicAtt	filesystem path	conf/	File with configuration of
ributesConfig		dynamicA	the dynamic part of the
		ttribute	XUUDB.
		sCfg.xml	
xuudb.protectAll	[true, false]	false	If true then access to both
			query and modify
			operations are protected by
			ACL. If false then only
			modification operations are
			protected.
xuudb.type	[dn]	dn	DEPRECATED and no
			longer required.

#### **Database settings**

XUUDB can be configured to use different database backends. Currently an embedded H2 database and external MySQL are supported. H2 database (the default) requires no additional configuration actions. In any case XUUDB will automatically create the required database tables.

For MySQL you have to properly set up the server and create a database. After installing and starting the MySQL server login to its using MySQL client as administrator and using a commands similar to the below ones, create a database and assign full access to a xuudb user.

```
create database xuudb;
grant all on xuudb.* to 'xuudbuser'@'127.0.0.1' identified ↔
by 'pass';
```

Of course you are free to choose different names for the user, password and database. If XU-UDB server is installed on other host then the proper address must be set instead of localhost.

Use the following properties to configure database connection from the XUUDB server. In case of external database pay attention to enter proper values.

Property name	Туре	Default value / mandatory	Description
	Date	ibase	1
xuudb.db.dialect	[h2, mysql]	h2	Database SQL dialect.
			Must match the selected
			driver, however sometimes
			more then one driver can be
			available for a dialect.
xuudb.db.driver	Class extending	org.h2.	Database driver class name.
	java.sql.Driver	Driver	This property is optional -
			if not set, then a default
			driver for the chosen
			database type is used.
xuudb.db.jdbcUrl	string	jdbc:h2:	Database JDBC URL.
		data/	
		xuudb2	
xuudb.db.	string	empty	Database password.
password		string	
xuudb.db.	string	sa	Database username.
username			

#### Configuring advanced HTTP server settings

UNICORE servers are using an embedded Jetty HTTP server. In most cases the default configuration should be perfectly fine. However, for some sites (e.g. experiencing an extremely high load) HTTP server settings can be fine-tuned with the following parameters.

Property name	Туре	Default value / mandatory	Description
xuudb.	string	*	CORS: comma separated
httpServer.CORS_			list of allowed HTTP
allowedHeaders			headers (default: any)

Property name	Туре	Default	Description
		value /	
		mandatory	
xuudb.	string	GET,PUT,	CORS: comma separated
httpServer.CORS_		POST,DEL	list of allowed HTTP verbs.
allowedMethods		ETE, HEAD	
xuudb.	string	*	CORS: allowed script
httpServer.CORS_			origins.
allowedOrigins			
xuudb.	[true, false]	false	CORS: whether preflight
httpServer.CORS_			OPTION requests are
chainPreflight			chained (passed on) to the
			resource or handled via the
			CORS filter.
xuudb.	string	Location	CORS: comma separated
httpServer.CORS_		,Cont	list of HTTP headers that
exposedHeaders		ent-Type	are allowed to be exposed
			to the client.
xuudb.	string	empty	Space separated list of SSL
httpServer.disab		string	cipher suites to be disabled.
ledCipherSuites			Names of the ciphers must
			adhere to the standard Java
			cipher names, available
			here:
			http://docs.oracle.com/-
			javase/8/docs/technotes/-
			guides/security/-
			SunProviders.html#SupportedCipherSuites
xuudb.	[true, false]	false	Control whether
httpServer.			Cross-Origin Resource
enableCORS			Sharing is enabled. Enable
			to allow e.g. accesing
			REST services from
			client-side JavaScript.

Property name	Туре	Default value / mandatory	Description
xuudb. httpServer. enableHsts	[true, false]	false	Control whether HTTP strict transport security is enabled. It is a good and strongly suggested security mechanism for all production sites. At the same time it can not be used with self-signed or not issued by a generally trusted CA server certificates, as with HSTS a user can't opt in to enter such site.
xuudb. httpServer. fastRandom	[true, false]	false	Use insecure, but fast pseudo random generator to generate session ids instead of secure generator for SSL sockets.
<pre>xuudb. httpServer.gzip. enable</pre>	[true, false]	false	Controls whether to enable compression of HTTP responses.
xuudb. httpServer.gzip. minGzipSize	integer number	100000	Specifies the minimal size of message that should be compressed.
<pre>xuudb. httpServer.highL oadConnections</pre>	integer number	200	If the number of connections exceeds this amount, then the connector is put into a special <i>low on</i> <i>resources</i> state. Existing connections will be closed faster. Note that the server will also go to the low on resources mode if there are no available threads in the pool. You can set this to 0 to disable the connections limit (and have only thread pool size governed limit). If set to a negative number then the <i>low on resources</i> mode won't be used at all.

Property name	Type	Default	Description
rioperej nume	-5.00	value /	Description
		mandatory	
xuudb. httpServer. lowResourceMaxId leTime	integer >= 1	100	In low resource conditions, time (in ms.) before an idle connection will time out.
xuudb. httpServer. maxIdleTime	integer >= 1	200000	Time (in ms.) before an idle connection will time out. It should be large enough not to expire connections with slow clients, values below 30s are getting quite risky.
xuudb. httpServer. maxThreads	integer number	255	Maximum number of threads to have in the thread pool for processing HTTP connections. Note that this number will be increased with few additional threads to handle connectors.
xuudb. httpServer. minThreads	integer >= 1	1	Minimum number of threads to have in the thread pool for processing HTTP connections. Note that this number will be increased with few additional threads to handle connectors.
xuudb. httpServer.requi reClientAuthn	[true, false]	true	Controls whether the SSL socket requires client-side authentication.
xuudb. httpServer. soLingerTime	integer number	-1	Socket linger time.
xuudb. httpServer. wantClientAuthn	[true, false]	true	Controls whether the SSL socket accepts (but does not require) client-side authentication.
xuudb. httpServer. xFrameAllowed	string	http:// localh ost	URI origin that is allowed to embed web interface inside a (i)frame. Meaningful only if the xFrameOptions is set to <i>allowFrom</i> . The value should be in the form: <i>http[s]://host[:port]</i>

Property name	Туре	Default value / mandatory	Description
xuudb. httpServer. xFrameOptions	[deny, sameOrigin, allowFrom, allow]	deny	Defines whether a clickjacking prevention should be turned on, by insertionof the X-Frame-Options HTTP header. The <i>allow</i> value disables the feature. See the RFC 7034 for details. Note that for the <i>allowFrom</i> you should define also the xFrameAllowed option and it is not fully supported by

#### Example

#### Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

In this example we will turn on compression of all responses bigger then 50kB (assuming that the client supports decompression). Additionally we are limiting the number of concurrent clients that can be served to more or less 50, while keeping 10 threads ready all the time to server new clients quicker.

```
jetty.gzip.enable=true
jetty.gzip.minGzipSize=51200
jetty.maxThreads=50
jetty.minThreads=10
```

#### Configuring PKI trust settings

Public Key Infrastructure (PKI) trust settings are used to validate certificates. This is performed, in the first place when a connection with a remote peer is initiated over the network, using the SSL (or TLS) protocol. Additionally certificate validation can happen in few other situations, e.g. when checking digital signatures of various sensitive pieces of data.

Certificates validation is primarily configured using a set of initially trusted certificates of so called Certificate Authorities (CAs). Those trusted certificates are also known as *trust anchors* and their collection is called a *trust store*.

Except of *trust anchors* validation mechanism can use additional input for checking if a certificate being checked was not revoked and if its subject is in a permitted namespace.

UNICORE allows for different types of trust stores. All of them are configured using a set of properties.

- *Keystore trust store* the only format supported in older UNICORE versions. Trusted certificates are stored in a single binary file in JKS or PKCS12 format. The file can be only manipulated using a special tool like JDK *keytool* or openssl (in case of PKCS12 format). This format is great if trust store should be in a single file or when compatibility with other Java solutions or older UNICORE releases is desired.
- OpenSSL trust store allows to use a directory with CA certificates stored in PEM format, under precisely defined names: the CA certificates, CRLs, signing policy files and namespaces files are named <hash>.0, <hash>.r0, <hash>.signing\_policy and <hash>.namespaces.
   Hash is the old hash of the trusted CA certificate subject name (in Openssl version > 1.0.0 use -suject\_hash\_old switch to generate it). If multiple certificates have the same hash then the default zero number must be increased. This format is the same as used by other then UNICORE popular middlewares as Globus and gLite. It is suggested when a common trust store with such middlewares is needed.
- *Directory trust store* the most flexible and convenient option, suggested for all remaining cases. It allows to use a list of wildcard expressions, concrete paths of files or even URLs to remote files as a set of trusted CAs and in the same way for the CRLs. With this trust store administrator can simply configure all files (or all with a specified extension) in a directory to be used as a trusted certificates.

Property name	Туре	Default value / mandatory	Description				
xuudb.	[ALLOW,	ALLOW	Controls whether proxy				
truststore.	DENY]		certificates are supported.				
allowProxy							
xuudb.	[keystore,	mandatory	The truststore type.				
truststore.type	openssl,	to be set					
	directory]						
xuudb.	integer number	600	How often the truststore				
truststore.			should be reloaded, in				
updateInterval			seconds. Set to negative				
			value to disable refreshing				
			at runtime. (runtime				
			updateable)				
	Directory t	Directory type settings					

In all cases trust stores can be (and by default are) configured to be automatically refreshed.

Property name	Туре	Default value / mandatory	Description	
<pre>xuudb. truststore. directoryConnect ionTimeout</pre>	integer number	15	Connection timeout for fetching the remote CA certificates in seconds.	
xuudb. truststore. directoryDiskCac hePath	filesystem path	-	Directory where CA certificates should be cached, after downloading them from a remote source. Can be left undefined if no disk cache should be used. Note that directory should be secured, i.e. normal users should not be allowed to write to it.	
xuudb. truststore.direc toryEncoding	[PEM, DER]	PEM	For directory truststore controls whether certificates are encoded in PEM or DER. Note that the PEM file can contain arbitrary number of concatenated, PEM-encoded certificates.	
<pre>xuudb. truststore.direc toryLocations.*</pre>	list of properties with a common prefix	-	List of CA certificates locations. Can contain URLs, local files and wildcard expressions. ( <i>runtime updateable</i> )	
Keystore type settings				
xuudb. truststore. keystoreFormat	string	-	The keystore type (jks, pkcs12) in case of truststore of keystore type.	
xuudb. truststore. keystorePassword	string	-	The password of the keystore type truststore.	
xuudb. truststore. keystorePath	string	-	The keystore path in case of truststore of keystore type.	
Openssl type settings				

Property name	Туре	Default	Description
1 0		value /	I.
		mandatory	
xuudb.	[true, false]	false	In case of openssl
truststore.opens			truststore, specifies whether
slNewStoreFormat			the trust store is in openssl
			1.0.0+ format (true) or
			older openssl 0.x format
			(false)
xuudb.	[GLOBUS_EUG	R HORMA ADPM	In case of openssl
truststore.	EU-	A_GLOBUS	truststore, controls which
opensslNsMode	GRIDPMA_GLC	BUS,	(and in which order)
-	GLOBUS,		namespace checking rules
	EUGRIDPMA,		should be applied. The
	GLOBUS_EUGR	IDPMA_REQ	U <b>RHQ</b> UIRE settings will
	EU-		cause that all configured
	GRIDPMA_GLC	BUS_REQUIE	Enamespace definitions files
	GLOBUS_REQU	IRE,	must be present for each
	EU-		trusted CA certificate
	GRIDPMA_REQ	UIRE,	(otherwise checking will
	EU-		fail). The AND settings will
	GRIDPMA_AND	_GLOBUS,	cause to check both existing
	EU-		namespace files. Otherwise
	GRIDPMA_AND	_GLOBUS_R	EQNE IRE, found is checked
	IGNORE]		(in the order defined by the
			property).
xuudb.	filesystem path	/etc/	Directory to be used for
truststore.		grid-sec	opeenssl truststore.
opensslPath		urity/	
		certific	
		ates	
	Revocatio	on settings	
xuudb.	integer number	15	Connection timeout for
truststore.crlCo			fetching the remote CRLs
nnectionTimeout			in seconds (not used for
			Openssl truststores)

Property name	Type	Default	Description
rioperej nume	-5.00	value /	Description
		mandatory	
xuudb.	filesystem path	-	Directory where CRLs
truststore			should be cached after
crlDiskCachePath			downloading them from
er i Diskedener den			remote source. Can be left
			undefined if no disk cache
			should be used. Note that
			directory should be
			secured i.e. normal users
			should not be allowed to
			write to it. Not used for
			Openest truststores
vuudh	list of		List of CPLs locations Can
truststoro	nroperties with	-	contain UPL s local files
arliogations *	a common		and wildcard expressions
CITEOCACIONS. *	prefix		Not used for Opensel
			truststores (runtime
			undataabla)
wuudh			General CPL handling
tructetoro	IF VALID	IF_VALID	mode The IF VALID
criModo	IGNOREI		setting turns on CPI
CIIMOUE	IONOKEJ		checking only in case the
			CRL is present
xuudh	integer number	600	How often CRLs should be
truststore crllin		000	updated in seconds Set to
dateInterval			negative value to disable
daternetivar			refreshing at runtime
			(runtime undateable)
xuudb.	integer number	3600	For how long the OCSP
truststore.			responses should be locally
ocspCacheTtl			cached in seconds (this is a
o cope cacino 1 o 1			maximum value, responses
			won't be cached after
			expiration)
xuudb.	filesystem path	-	If this property is defined
truststore.			then OCSP responses will
ocspDiskCache			be cached on disk in the
000p210//040//0			defined folder.
xuudb.	list of	-	Optional list of local OCSP
truststore.ocspl	properties with		responders
ocalResponders.	a common		<b>T</b>
<number></number>	prefix		

Property name	Туре	Default value / mandatory	Description
xuudb.	[REQUIRE,	IF_AVAIL	General OCSP ckecking
truststore.	IF_AVAILABLE,	ABLE	mode. REQUIRE should
ocspMode	IGNORE]		not be used unless it is
			guaranteed that for all
			certificates an OCSP
			responder is defined.
xuudb.	integer number	10000	Timeout for OCSP
truststore.			connections in miliseconds.
ocspTimeout			
xuudb.	[CRL_OCSP,	OCSP_CRL	Controls overal revocation
truststore.	OCSP_CRL]		sources order
revocationOrder			
xuudb.	[true, false]	false	Controls whether all
truststore.			defined revocation sources
revocationUseAll			should be always checked,
			even if the first one already
			confirmed that a checked
			certificate is not revoked.

# Examples

#### Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

Directory trust store, with a minimal set of options:

```
truststore.type=directory
truststore.directoryLocations.l=/trust/dir/*.pem
truststore.crlLocations=/trust/dir/*.crl
```

Directory trust store, with a complete set of options:

```
truststore.type=directory
truststore.allowProxy=DENY
truststore.updateInterval=1234
truststore.directoryLocations.1=/trust/dir/*.pem
truststore.directoryLocations.2=http://caserver/ca.pem
truststore.directoryEncoding=PEM
truststore.directoryConnectionTimeout=100
```

```
truststore.directoryDiskCachePath=/tmp
truststore.crlLocations.1=/trust/dir/*.crl
truststore.crlLocations.2=http://caserver/crl.pem
truststore.crlUpdateInterval=400
truststore.crlMode=REQUIRE
truststore.crlConnectionTimeout=200
truststore.crlDiskCachePath=/tmp
```

#### Openssl trust store:

```
truststore.type=openssl
truststore.opensslPath=/truststores/openssl
truststore.opensslNsMode=EUGRIDPMA_GLOBUS_REQUIRE
truststore.allowProxy=ALLOW
truststore.updateInterval=1234
truststore.crlMode=IF_VALID
```

#### Java keystore used as a trust store:

```
truststore.type=keystore
truststore.keystorePath=src/test/resources/certs/truststore. ↔
jks
truststore.keystoreFormat=JKS
truststore.keystorePassword=xxxxxx
```

#### Configuring the credential

UNICORE uses private key and a corresponding certificate (called together as a *credential*) to identify users and servers. Credentials might be provided in several formats:

- Credential can be obtained from a keystore file, encoded in JKS or PKCS12 format.
- Credential can be loaded as a pair of PEM files (one with private key and another with certificate),
- or from a pair of DER files,
- or even from a single file, with PEM-encoded certificates and private key (in any order).

The following table list all parameters which allows for configuring the credential. Note that nearly all options are optional. If not defined, the format is tried to be guessed. However some credential formats require additional settings. For instance if using *der* format the *keyPath* is mandatory as you need two DER files: one with certificate and one with the key (and the latter can not be guessed).

Impletely matheTypeDescriptionvalue / mandatoryvalue / mandatoryvalue / mandatoryxuudb. credential.pathfilesystem pathmandatory to be setCredential location. In case of jks, pkcs12 and pem store it is the only location required. In case when credential is provided in two files, it is the certificate file path.xuudb. credential.[jks, pkcs12, der, pem]-Format of the credential. It is guessed when not given. Note that pem might be either a PEM keystore with certificates and keys (in PEM files (one with certificate and second with private key).xuudb. credential.string-Password required to load the credential.	Property name	Type	Default	Description
xuudb. credential.pathfilesystem path filesystem pathmandatory mandatory to be setCredential location. In case of jks, pkcs12 and pem store it is the only location required. In case when credential is provided in two files, it is the certificate file path.xuudb.[jks, pkcs12, der, pem]-format[jks, pkcs12, der, pem]-format <th> open of mane</th> <th>-5 P*</th> <th>value /</th> <th>2.0001.19.001</th>	open of mane	-5 P*	value /	2.0001.19.001
xuudb. credential.pathfilesystem path ito be setmandatory to be setCredential location. In case of jks, pkcs12 and pem store it is the only location required. In case when credential is provided in two files, it is the certificate file path.xuudb. credential.[jks, pkcs12, der, pem]-Format of the credential. It is guessed when not given. Note that pem might be either a PEM keystore with certificates and keys (in PEM format) or a pair of PEM files (one with certificate and second with private key).xuudb. credential.string-Password required to load the credential.			mandatory	
credential.pathto be setof jks, pkcs12 and pem store it is the only location required. In case when credential is provided in two files, it is the certificate file path.xuudb.[jks, pkcs12, der, pem]-Format of the credential. It is guessed when not given. Note that pem might be either a PEM keystore with certificates and keys (in PEM format) or a pair of PEM files (one with certificate and second with private key).xuudb.string-Password required to load the credential.	xuudb.	filesystem path	mandatory	Credential location. In case
xuudb.[jks, pkcs12, der, pem]-Format of the credential. It is guessed when not given. Note that pem might be either a PEM keystore with certificates and keys (in PEM format) or a pair of PEM files (one with certificate and second with private key).xuudb.string-string-string-string-string-string-string-string-string-string-string-string-stri	credential.path		to be set	of <i>jks</i> , <i>pkcs12</i> and <i>pem</i> store
xuudb.[jks, pkcs12, der, pem]-Format of the credential. It is guessed when not given. Note that pem might be either a PEM keystore with certificates and keys (in PEM format) or a pair of PEM files (one with certificate and second with private key).xuudb.string-xuudb.string-xuudb.string-				it is the only location
xuudb.[jks, pkcs12, der, pem]-Format of the credential. It is guessed when not given. Note that pem might be either a PEM keystore with certificates and keys (in PEM format) or a pair of PEM files (one with certificate and second with private key).xuudb.string-Password required to load the credential.				required. In case when
xuudb.[jks, pkcs12, der, pem]-Format of the credential. It is guessed when not given. Note that pem might be either a PEM keystore with certificates and keys (in PEM format) or a pair of PEM files (one with certificate and second with private key).xuudb.string-xuudb.string-credentialPassword required to load the credential.				credential is provided in
xuudb.[jks, pkcs12, der, pem]-Format of the credential. It is guessed when not given. Note that pem might be either a PEM keystore with certificates and keys (in PEM format) or a pair of PEM files (one with certificate and second with private key).xuudb.string-Password required to load the credential.				two files, it is the certificate
xuudb.[jks, pkcs12,-Format of the credential. Itcredential.der, pem]is guessed when not given.formatder, pem]Note that pem might beeither a PEM keystore witheither a PEM keystore withcertificates and keys (inPEM format) or a pair ofPEM files (one withertificate and second withprivate key).ratingxuudb.string-credential.Image: Constraint of the credential.		Film place 12		file path.
format       act, pennj       is guessed when not given.         format       Note that pem might be       either a PEM keystore with         certificates and keys (in       PEM format) or a pair of         PEM files (one with       certificate and second with         private key).       string       -         credential.       -       Password required to load	arodontial	JKS, PKCS12,	-	is guessed when not given
xuudb.       string       -       Password required to load         credential.       the credential.       -       Password required to load	format			Note that <i>nem</i> might be
xuudb.       string       -       Password required to load         credential.       the credential.       -       Password required to load	rormae			either a PEM keystore with
xuudb.       string       -       Password required to load         credential.       -       the credential.				certificates and keys (in
xuudb.     string     -     Password required to load       credential.     the credential.				PEM format) or a pair of
xuudb.     string     -     Password required to load       credential.     -     the credential.				PEM files (one with
xuudb.string-Password required to loadcredentialthe credential.				certificate and second with
xuudb.string-Password required to loadcredential.the credential.				private key).
credential. the credential.	xuudb.	string	-	Password required to load
	credential.			the credential.
password	password			
xuudb. string - Location of the private key	xuudb.	string	-	Location of the private key
kowPath the main credential	credential.			the main credential
(applicable for <i>nem</i> and <i>der</i>	keyratli			(applicable for <i>pem</i> and <i>der</i>
types only).				types only).
xuudb. string - Private key password,	xuudb.	string	-	Private key password,
credential. which might be needed	credential.			which might be needed
keyPassword only for <i>jks</i> or <i>pkcs12</i> , if	keyPassword			only for <i>jks</i> or <i>pkcs12</i> , if
key is encrypted with				key is encrypted with
different password then the				different password then the
main credential password.				main credential password.
xuudb. string - Keystore alias of the key	xuudb.	string	-	Keystore alias of the key
credential. entry to be used. Can be	credential.			entry to be used. Can be
ReyAllas Ignored If the ReyStore	ĸeyAllas			ignored if the keystore
Only applicable for <i>ibs</i> and				Only applicable for <i>iks</i> and
nkcs12.				<i>pkcs12.</i>

#### Examples

#### Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

Credential as a pair of DER files:

```
credential.format=der
credential.password=the\!njs
credential.path=/etc/credentials/cert-1.der
credential.keyPath=/etc/credentials/pk-1.der
```

Credential as a JKS file (credential type can be autodetected in almost every case):

```
credential.path=/etc/credentials/server1.jks
credential.password=xxxxxx
```

# **Dynamic mappings configuration**

Dynamic mappings are configured with a set of rules. When designing rules it is good to remember that all users, which will be evaluated, were already successfully authorized.

Each rule has a condition which selects users and a list of mappings which should be applied for the selected users. Example conditions (in English):

- all members of a /vo.wonderworld.gov
- all (authorized) users
- all users having extra attribute *matlabAllowed* with any value AND being member of a subgroup of /vo.wonderworld.gov/dynamic/

Example mappings (in English):

- add user a supplementary group *matlab*
- · assign uid from a pool of existing uids
- assign a fixed gid grid
- · invoke an external program and use its standard output as users gid

Precisely speaking, a mapping must have defined:

- what attribute it maps: uid, (primary)gid or supplementaryGids,
- using what method: fixed, pool or script

Additionally one can define an optional parameter stating if the mapping should overwrite an attribute value which was previously set (either by an earlier rule or assigned using a different attribute source).

As it was mentioned there are three kinds of mappings. Let's shortly introduce them one by one.

### **Fixed mappings**

*Fixed mappings* are the most basic option. The mapping is formed by a simple assignment of a fixed value. It can be used to:

- assign a common (shared!) uid to selected users (rarely used)
- assign a fixed gid to selected users (very useful to assign a gid to all Grid users, or all members of a VO)
- assign some supplementary gids to selected users (useful to provide additional local permissions to users having a special role/attributes/etc.).

The example in the pool mappings section contains also a fixed mapping.

#### Script mappings

*Script mappings* are the "Do It Yourself" mechanism. You can provide a command line which will be parsed and invoked. The application must return (on its standard output) a string with a mapping result (depending on what is mapped - gid, uid or a space separated list of supplementary gids). Of course the script can be informed who is actually being mapped, by using parameters enclosed in  $\{$   $\}$ . The list of available parameters is given below.

- userDN user's DN
- issuerDN user's certificate issuer's DN
- role user's role
- vo user's selected VO
- extraAttributes map with extra attributes, names are the keys
- xlogin user's uid (if already established)
- gid user's gid (if already established)

- supplementaryGids user's supplementary gids (if already established)
- xloginSet whether uid was set
- gidSet whether gid was set
- dryRun whether the current invocation is only a simulation, and shouldn't affect any persisted system settings.

The example below contains also a script mapping.

#### **Pool mappings**

Finally the *pool mappings* are both flexible and relatively easy to use --- it is the most advanced mapping type. Using the pool mapping you have to prepare a set of reserved identifiers (uids or gids depending on what is mapped). The related system accounts can be precreated or can be created on-demand. The pool mapping is configured with an additional, very important parameter: pool key. Pool key is a name of one of the user's attributes: *userDN*, *issuerDN* (DN of CA which issued user's certificate), *role*, *vo* or any other generic user's attribute.

To explain how the pool works let's assume that key is set to *userDN*. Then the pool will map a user as follows: first it is checked if there is an existing mapping bound to the user's DN. If it is found then it is simply returned. If not (the user is trying to use the site for the first time) a new identifier is selected from the pool, and stored under the key being the user's DN. Then the new identifier is returned.

Therefore all users having the same value of the pool key will get the same mapping and vice versa. If DN is the key then all users will have a distinct mapping (useful for uids or for gids, if every user should get a unique one). If for instance a VO is the key then all VO members will have the same mapping (useful for gid, or for uid if all VO members should have the same user account).

The following example should help to understand those concepts and is also providing a basic syntax reference:

```
<?xml version="1.0" encoding="UTF-8"?>
<dynamicAttributes xmlns="http://unicore.eu/xuudb/ \leftarrow
dynamicAttributesRules"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    </rules>
    <!-- all members of the vo /vo.wonderworld.gov should have a \leftarrow
        common uid 'shared_user'-->
        <rule>
            <condition>vo.matches("/vo.wonderworld.gov/.*")</condition>
            <mapping type="fixed" maps="uid">shared_user</mapping>
        </rule>
        <!-- all users with a role 'admin' should get a primary gid \leftarrow
        from the 'admins-pool' pool.</pre>
```

```
For pools the 'maps' parameter is optional - it is better to \leftrightarrow
     specify it in the pool definition,
 below. -->
  <rule>
    <condition>role="admin"</condition>
    <mapping type="pool">admins-pool</mapping>
  </rule>
  <!-- all users from the /biology VO get an uid from the pool \ \leftrightarrow
     and a fixed primary gid 'biol' -->
  <rule>
    <condition>vo.matches("/biology/.*")</condition>
    <mapping type="pool">biology-uids-pool</mapping>
    <mapping type="fixed" maps="gid">biol</mapping>
  </rule>
  <!-- complicated condition: all users who have a generic \ \leftrightarrow
      attribute 'matlabAllowed' set AND the value
      of this attribute is 'true' get a supplementary group ' \leftrightarrow
         matlab' -->
  <rule>
    <condition>attributes["matlabAllowed"] != null and attributes 
        ["matlabAllowed"].contains("true")</condition>
    <mapping type="fixed" maps="supplementaryGids">matlab</ \leftrightarrow
       mapping>
  </rule>
  <!-- all (authorized) users, who do not have an uid set ( \hookleftarrow
     overwriteExisting=false)
      should have an uid assigned by a script /usr/local/bin/ \leftarrow
         create-mapping.pl. The script will be called
      with two arguments: user's DN and VO.
  <rule>
    <condition>true</condition>
    <mapping type="script" maps="uid" overwriteExisting="false">/ <--
        usr/local/bin/create-mapping.pl "${userDN}" "${vo}" </ ↔
        mapping>
  </rule>
</rules>
<!-- Here come pools -->
<pools>
  <!-- pool 'admins-pool' maps gids. The list of gids provides \, \leftrightarrow \,
     groups which were
 pre-created in the system. The gids will be stored per-user dn, \leftrightarrow
      so every admin will get another group.
 Finally the list of gids uses special expressions where number \ \hookleftarrow
     ranges are provided.
 <pool id="admins-pool" type="gid" key="dn" precreated="true">
```

```
<id>admin_grp[1-100]</id>
<id>admin_grp[200-1000]</id>
</pool>
<!-- This pool identifiers are loaded from an external file -->
<pool id="biology-uids-pool" type="uid" key="dn" precreated=" 
    true">
        file>src/test/resources/externalUidsPool</file>
</pool>
</pools>
</dynamicAttributes>
```

Usage of pools brings several issues regarding old mappings removal and notifications about pools getting empty. In the first case it suggested not to remove the users for the time a VO or Grid is supported: it is a simplest approach, and nowadays operating systems can support thousands of uids without any problem (Linux can have 32bit uid numbers).

In case a site wants to recycle mappings, XUUDB offers the following mechanism:

- Inactive mappings can be automatically (after a configurable time threshold) or manually (using the admin client) *frozen*. An identifier belonging to a frozen mapping is still assumed to be occupied, but the mapped user won't have it assigned (in the unprobable case that she returns to the site). Freezing is introduced to give a time for tidying up local resources assigned to the identifier. Such cleaning must be done manually and should include removal of all owned files and killing any processes. Of course this depends whether the identifier was a gid or uid. Also please note that in case of clusters, all nodes should be cleaned up.
- After the clean up is done, the frozen mapping can be removed, again manually using the admin client or automatically, after staying in the frozen state for a specified amount of time. Note that it is impossible to remove an alive mapping.

If administrator is able to provide scripts which performs cleanup, then it is possible to invoke them upon pool mapping freezing and automate the whole process. In a similar way other handlers may be configured and XUUDB will invoke them to notify about mappings removal, assignment of a new mapping (useful when accounts are not pre-created but should be created on demand) and also when a pool is getting empty.

The following example shows all the possible handlers and lists arguments which are passed to them. As it can be seen all pool options including handlers, can be configured globally or per-pool.

```
<!-- in seconds: automatic freezeing (time measured from \leftrightarrow
       last mapping use)... -->
   <automaticFreezeAfter>3600000</automaticFreezeAfter>
   <!-- ... and final removal (time measurd from mapping \leftrightarrow
       freeze) -->
   <automaticDeleteAfter>36000</automaticDeleteAfter>
   <!-- when less then this free mappings are left generate a \ \leftrightarrow
       warning -->
   <emptyWarningAbsolute>20</emptyWarningAbsolute>
   <!-- when less then this percent of free mappings is left \ \hookleftarrow
       generate a warning -->
   <emptyWarningPercent>5</emptyWarningPercent>
   <!-- timeout for running ALL external programms -->
   <handlerInvocationTimeLimit>10000</ <--
       handlerInvocationTimeLimit>
   <!-- Various handlers. Arguments are pool.getId(), pool. \hookleftarrow
       getType().toString(),
                                      bean.getEntry(), oldSec+"" ↔
                                          -->
   <!-- Handler invoked before freezing an account.
Arguments: <poolId> <poolType> <identifier> < ↔
    inactiveForInSeconds>
If handler returns a non-zero exit status then the freezing is \hookleftarrow
    skipped
(unless invoked by admin-client).
   -->
   <handlerAboutToFreeze>/opt/handlers/releaseAccountResources \leftrightarrow
       .sh</handlerAboutToFreeze>
   <!-- Handler invoked before deleting a frozen identifier.
        Arguments: <poolId> <poolType> <identifier> < ↔
            frozenForInSeconds>
        If handler returns a non-zero exit status then the \,\, \leftrightarrow \,\,
            deletion is skipped
         (unless invoked by admin-client).
         -->
   <handlerAboutToDelete>/opt/handlers/notifyAccountRecycled. \leftarrow
       sh</handlerAboutToDelete>
   <!-- Handler invoked when an identified from the uids pool \,\leftrightarrow\,
       is going to be used for the first time
   (or for the first time after deleting it), if the pool is \leftrightarrow
       set as not pre-created.
           Arguments: <poolId> <uid> <key>
   -->
   <handlerCreateSystemUid>/opt/handlers/adduser.sh</ <>
       handlerCreateSystemUid>
```

```
<!-- Handler invoked when an identified from the gids pool \,\leftrightarrow\,
            is going to be used for the first time
        (or for the first time after deleting it), if the pool is \ \leftarrow
            set as not pre-created.
                Arguments: <poolId> <gid> <key>
        -->
        <handlerCreateSystemGid>/opt/handlers/addgroup.sh</ \leftarrow
            handlerCreateSystemGid>
        <!-- Handler invoked when a pool warning threshold is \, \leftarrow \,
            exceeded.
             Arguments: <poolId> <poolType> <remainingFreeIds>
        -->
        <handlerPoolGettingEmpty>/opt/handlers/notifyNearlyEmpty.sh \hookleftarrow
            </handlerPoolGettingEmpty>
        <!-- Handler invoked when a pool gets empty.
             Arguments: <poolId> <poolType>
        -->
        <handlerPoolEmpty>/opt/handlers/notifyEmpty.sh</ <->
            handlerPoolEmpty>
  </defaultConfiguration>
  <rules>
       <!-- some rules ..... -->
  </rules>
  <pools>
        <!-- Pool can overwrite any of the global configuration \ \leftrightarrow
           options -->
    <pool id="admins-pool" type="gid" key="dn" precreated="true">
      <configuration>
         <!-- disable automatic freezing for this pool -->
                 <automaticFreezeAfter>-1</automaticFreezeAfter>
      </configuration>
      <id>admin_grp[1-100]</id>
      <id>admin_grp[200-1000]</id>
    </pool>
  </pools>
</dynamicAttributes>
```

# Starting the XUUDB server

Start the server with

BIN/start.sh

In case if XUUDB was installed with binary package use: /etc/init.d/unicore-xuudb start

# Stopping the server

Stop the server with

BIN/stop.sh

This sends a TERM signal to the XUUDB process. Please do not use kill -9 to stop XU-UDB, to avoid corrupting the database.

In case if XUUDB was installed with binary package use:

/etc/init.d/unicore-xuudb stop

# Logging

UNICORE uses the Log4j logging framework. It is configured using a config file. By default, this file is found in components configuration directory and is named logging.propert ies. The config file is specified with a Java property log4j.configuration (which is set in startup script).

Several libraries used by UNICORE also use the Java utils logging facility (the output is twolines per log entry). For convenience its configuration is also controlled in the same logging. properties file and is directed to the same destination as the main Log4j output.

#### Note

You can change the logging configuration at runtime by editing the logging.properties file. The new configuration will take effect a few seconds after the file has been modified.

By default, log files are written to the the LOGS directory.

The following example config file configures logging so that log files are rotated daily.

```
# Set root logger level to INFO and its only appender to A1.
log4j.rootLogger=INFO, A1
# A1 is set to be a rolling file appender with default params
log4j.appender.A1=org.apache.log4j.DailyRollingFileAppender
log4j.appender.A1.File=logs/uas.log
#configure daily rollover: once per day the uas.log will be copied
#to a file named e.g. uas.log.2008-12-24
```

```
log4j.appender.A1.DatePattern='.'yyyy-MM-dd
# A1 uses the PatternLayout
log4j.appender.A1.layout=org.apache.log4j.PatternLayout
log4j.appender.A1.layout.ConversionPattern=%d [%t] %-5p %c{1} %x - 
%m%n
```

# Note

In Log4j, the log rotation frequency is controlled by the DatePattern. Check http://logging.apache.org/log4j/1.2/apidocs/org/apache/log4j/DailyRollingFileAppender.html for the details.

For more info on controlling the logging we refer to the log4j documentation:

- PatternLayout
- RollingFileAppender
- DailyRollingFileAppender

Log4j supports a very wide range of logging options, such as date based or size based file rollover, logging different things to different files and much more. For full information on Log4j we refer to the publicly available documentation, for example the Log4j manual.

#### Logger categories, names and levels

Logger names are hierarchical. In UNICORE, prefixes are used (e.g. "unicore.security") to which the Java class name is appended. For example, the XUUDB connector in UNICORE/X logs to the "unicore.security.XUUDBAuthoriser" logger.

Therefore the logging output produced can be controlled in a fine-grained manner. Log levels in Log4j are (in increasing level of severity):

# TRACE on this level *huge* pieces of unprocessed information are dumped, # DEBUG on this level UNICORE logs (hopefully) admin-friendly, verbose information, useful for hunting problems, # INFO standard information, not much output, # WARN warnings are logged when something went wrong (so it should be investigated), but recovery was possible, # ERROR something went wrong and operation probably failed, # FATAL something went really wrong - this is used very rarely for critical situations like server failure.

For example, to debug a security problem in the UNICORE security layer, you can set:

log4j.logger.unicore.security=DEBUG

If you are just interested in details of credentials handling, but not everything related to security you can use the following:

```
log4j.logger.unicore.security=INFO
log4j.logger.unicore.security.CredentialProperties=DEBUG
```

so the XUUDBAuthoriser will log on DEBUG level, while the other security components log on INFO level.

#### Note

(so the full category is printed) and turn on the general DEBUG logging for a while (on unicore). Then interesting events can be seen and subsequently the logging configuration can be fine tuned to only show them.

Several logging categories common in XUUDB:

Log category	Description	
unicore	All of UNICORE	
unicore.security	Security layer	
unicore.client	Client calls (to other servers)	
unicore.xuudb	XUUDB related	
unicore.xuudb.server	XUUDB server	
unicore.xuudb.server.db	XUUDB server database layer	
unicore.xuudb.client	XUUDB admin client	

# The admin client

The admin client is used to edit the XUUDB, using a web service interface. It is configured in the file CONF/xuudb\_client.conf. Client is invoked using the following pattern:

ADMIN <command> <options>

You can get detailed usage info by calling the admin script without any options. As it was noted above the actual utility path is dependent on how XUUDB was installed: it is either /usr/sbin/unicore-xuudb-admin or INST/bin/admin.sh.

#### Note

to switch on the confirmation message asked by the add command, edit the admin.sh script, so that the xuudb.batch property is set to false.

The client configuration requires the URL of the XUUDB server in the property xuudb.add ress and in case of secure HTTPS connections also a configuration truststore and credential. The settings are exactly the same as in case of the XUUDB server, so refer to its documentation: Section 4.3.4.

# Configuring advanced HTTP client settings

UNICORE client stack can be configured with several advanced options. In most cases you can skip this section as defaults are fine.

The following table lists all available options. A special note for the *http*.\* properties: those are passed to the Apache Commons HTTP Client library. Therefore it is possible to configure all relevant options of the client. The options are listed under this address: http://hc.apache.org/-httpclient-3.x/preference-api.html Also see the example below.

Property name	Туре	Default	Description
		value /	
		mandatory	
xuudb.client.	[true, false]	true	Controls whether signing of
digitalSigningEn			key web service requests
abled			should be performed.
xuudb.client.	[true, false]	false	Whether HTTP basic
httpAuthnEnabled			authentication should be
			used.
xuudb.client.	string	empty	Password for use with
httpPassword		string	HTTP basic authentication
			(if enabled).
xuudb.client.	string	empty	Username for use with
httpUser		string	HTTP basic authentication
			(if enabled).
xuudb.client.	string	empty	Space separated list of
inHandlers		string	additional handler class
			names for handling
			incoming WS messages
xuudb.client.	integer number	3	Controls how many times
maxWsCallRetries			the client should try to call
			a failing web service. Note
			that only the transient
			failure reasons cause the
			retry. Note that value of 0
			enables unlimited number
			of retries, while value of 1
			means that only one call is
			tried.
xuudb.client.	[true, false]	false	Controls whether messages
messageLogging			should be logged (at INFO
			level).
xuudb.client.	string	empty	Space separated list of
outHandlers		string	additional handler class
			names for handling
			outgoing WS messages

Property name	Type	Default	Description
Troperey nume	-500	value /	Description
		mandatory	
xuudb.client.	[true, false]	true	Controls whether security
securitySessions			sessions should be enabled.
xuudb.client.	[NONE,	WARN	Controls whether server's
serverHostnameCh	WARN, FAIL]		hostname should be
ecking			checked for matching its
			certificate subject. This
			verification prevents
			man-in-the-middle attacks.
			If enabled WARN will only
			print warning in log, FAIL
			will close the connection.
xuudb.client.	[true, false]	true	Controls whether SSL
sslAuthnEnabled			authentication of the client
			should be performed.
xuudb.client.	[true, false]	true	Controls whether the
sslEnabled			SSL/TLS connection mode
			is enabled.
xuudb.client.	integer number	10000	Amount of milliseconds to
wsCallRetryDelay			wait before retry of a failed
			web service call.
	HTTP clie	ent settings	
xuudb.client.	[true, false]	true	If set to false, then the
http.allow-			client will not use HTTP
chunking	Fr C 1 1		1.1 data chunking.
xuudb.client.	[true, false]	false	If set to true then the client
nttp.connection-			will send connection close
CLOSE			neader, so the server will
wundb aliant	intagar numbar	20000	Timeout for the connection
xuudb.client.	integer number	20000	astablishing (ma)
timoout			establishing (ins)
vuudb cliopt	integer number	6	How many connections per
http mayPerPoute	integer number	0	host can be made. Note:
neep.maxrerNouce			this is a limit for a single
			client object instance
xuudh client	integer number	3	Maximum number of
http	integer number		allowed HTTP redirects
maxRedirects			
xuudb.client.	integer number	20	How many connections in
http.maxTotal		-	total can be made. Note:
T			this is a limit for a single
			client object instance.
			cheft object instance.

Property name	Туре	Default value / mandatory	Description
<pre>xuudb.client. http.socket. timeout</pre>	integer number	0	Socket timeout (ms)
	HTTP pro	xy settings	
xuudb.client. http. nonProxyHosts	string	-	Space (single) separated list of hosts, for which the HTTP proxy should not be used.
<pre>xuudb.client. http.proxy. password</pre>	string	-	Relevant only when using HTTP proxy: defines password for authentication to the proxy.
xuudb.client. http.proxy.user	string	-	Relevant only when using HTTP proxy: defines username for authentication to the proxy.
xuudb.client. http.proxyHost	string	-	If set then the HTTP proxy will be used, with this hostname.
xuudb.client. http.proxyPort	integer number	-	HTTP proxy port. If not defined then system property is consulted, and as a final fallback 80 is used.
<pre>xuudb.client. http.proxyType</pre>	string	HTTP	HTTP proxy type: HTTP or SOCKS.

# Example

#### Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

Here we are setting an extremely short connection and socket timeouts for the clients calls, using the Apache HTTP client parameters. Additionally server hostname to certificate subject name checking is set to cause connections failures, preventing man in the middle attacks.

client.http.connection.timeout=2000
client.http.socket.timeout=2000
client.serverHostnameChecking=FAIL

#### Commands

The help with examples is provided for each command. You can use helpAll to print a reference documentation for all commands. Selected commands are also described below.

```
[classic]
  add
  adddn
  check-cert (chc)
  check-dn (chdn)
  export
 import
 list
  remove
 update
[dynamic]
  findMapping (fm)
  findReverseMapping (fr)
  freezeMappings
  getDynamicAttributes (getDyn)
  listMappings (lm)
 listPools (lp)
  removeMappings
  removePool (rmp)
 simulate (sim)
[other]
 help
 helpAll
```

### Note

when the server runs in dn mode you can use dn= parameter for remove, list and update

# Common options:

#### gcID

The so-called "grid component ID" is used to group entries, and must match the setting in the UNICORE/X configuration file uas.config. For example if you have two systems with different user name mappings, you can handle both with a single XUUDB, since you can store two user name mappings for each certificate, by choosing a different gcID for both systems. When updating xuudb entries, the special gcid \* can be used as wildcard for updating user entries on all systems.

# pemfile

A file containing the public key in PEM format

#### DN

The distinguished name of a user

#### xlogin

xlogins (from UNIX login) are used for incarnation. Grid user's request which results in invocation of operations on a target system (usually through BSS) must be mapped to a local UNIX user. This attribute specifies the XLogins which are valid for the user. The first one is also used as a default one, if user does not request a particular one. Multiple logins can be specified using a :

#### project

Defines a primary group UNIX group for a user. If it is undefined then a default group for the XLogin is used.

#### role

The usual roles in UNICORE are user for a normal user, and admin for an administrator. Custom roles can be added, and can be assigned permissions in the UNICORE/X security policy file.

# Adding entries using add or adddn

Example using a pem file:

\$> ADMIN add DEMO-SITE /path/to/usercert.pem userlogin user

Example using the DN (works only if server runs in DN mode):

```
$> ADMIN adddn DEMO-SITE "CN=John Doe, O=Test Inc" userlogin ↔
user
```

## Note

When extracting the DN from a certificate file using OpenSSL, make sure to use the RFC2 253 option, for example:

```
openssl x509 -in demouser.pem -noout -subject -nameopt ↔ RFC2253
```

## Checking the content

Apart from list, you can use the check-cert and check-dn commands to see what the XUUDB contains for a certain certificate or DN.

# **Removing entries**

HINT: before removing you can check with the list command which takes the same parameters, that your are removing the correct entries.

To remove all entries from xuudb (you will have to confirm this)

```
$> ADMIN remove ALL
```

To remove some entries, you have to specify attributes.

To remove a user with cert cert.pem at gcid MYSITE:

\$> ADMIN remove gcid=id001 pemfile=/path/cert.pem

To remove all users from gcid OLDMACHINE:

```
$> ADMIN remove gcid=OLDMACHINE
```

To remove a user with xlogin jdoe from all gcids:

```
$> ADMIN remove xlogin=jdoe
```

etc...

# Exporting/importing

The export command creates a csv file, which will contain the complete XUUDB database:

```
$> ADMIN export uudb.csv
```

If the file already exists, the export tool will complain. To override this, please specify the overwrite option, e.g.

```
$> ADMIN export uudb.csv overwrite
```

The import command takes the a csv file (as generated by export) and imports all entries. Already existing entries will not be changed. To do updates, execute admin.sh remove ALL before, or specify clearDB as a second argument

```
$> ADMIN import uudb.csv
```

# **Updating entries**

The update command can be used to modify existing entries, for example to replace the certificate or the login. For example,

\$> ADMIN update DEMO-SITE certs/demouser.pem xlogin=jb007

would update the entry identified by the gcID *DEMO-SITE* and the given pem file, and assign a new xlogin. If you want to update a user's entry on all the sites, you would use

```
$> ADMIN update \* certs/demouser.pem xlogin=jb007
```

Note that the wildcard \* is a special character for the shell and needs to be escaped with a backslash.